

# Safety data sheet

Complies with Regulation (EC) No. 1907/2006 (REACH) as amended by Regulation (EU) 2015/830

# Food grade ARGON

Issue date: 10/14/2021 Revision date: 10/14/2021 Version: 6.0

SDS reference: EIGA003A

# SECTION 1: Identification of the substance/mixture and company/undertaking

### 1.1. Product identifier

Trade name ARGON MSDS No. EIGA003A

Chemical description

CAS number: 7440-37-1

N°ONE: 1006

EC number: 231-147-0

Registration number Listed in Annex IV/V of REACH, exempt from registration

Chemical formula Ar

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant uses identified Industrial and professional. Carry out a risk analysis before use

Test or calibration gas Purge, dilution, inerting gas. Protective gas for welding processes.

Laboratory use

Use in the manufacture of electronic or photovoltaic components.

Food applications

Contact the supplier for more information on use

Uses advised against Consumer use

### 1.3. Information regarding the supplier of the safety data sheet

Company identification SARL RAYANOX

ZA Bethioua Wilaya of Oran, Algeria

Tel: 041-79-35-22 Fax: 041-79-32-23 Contact@rayanox.co sarlrayanox@gmail.com

1.4. Emergency call number

Emergency call number Tel: +21365550342

### **SECTION 2: Hazard Identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]
Physical hazards
Gas under pressure: Compressed gas

H280

#### 2.2. Label elements

### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Attention

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage: P403 - Store in a well-ventilated area.

2.3. Other dangers

: Asphyxiant at high concentration.

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

NAME	Product identifier	Impurity					%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
<u>Argon</u>	(CAS No.) 7440-37-1 (EC No.) 231-147-0	<u>H2O</u> <u>≤500pp</u> <u>m</u>	<u>02</u> <u>≤1ppm</u>	<u>H2</u> ≤1ppm	<u>N2</u> ≤1ppm	<u>THC</u> ≤100ppm	<u>&gt;99,999</u>	Press. Gas (Ref. Liq.), H281

### 3.2. Mixtures: Not applicable

### **SECTION 4: First aid**



Issue date: 10/14/2021 Replaces sheet: 4.0 Revision date: 10/14/2021 Version: 6.0

SDS reference: EIGA003A

4.1. Description of first aid

Skin contact

Eye contact

Inhalation Move the victim to an uncontaminated area, putting on a breathing apparatus

Individual autonomy (ARI). Keep the victim warm and at rest. Call a doctor.

Perform cardiopulmonary resuscitation if the victim stops breathing.

Evacuate the victim to a non-contaminated area. No adverse effects expected with this product. No adverse effects expected with this product. Ingestion is not considered a possible mode of exposure

Ingestion 4.2. Most important symptoms and effects, both acute and delayed

May cause asphyxiation at high concentrations. Symptoms may include loss of consciousness or

motor skills. The victim may not be aware of the asphyxiation.

Refer to section 11.

4.3. <u>Indication of any immediate medical attention and special treatment needed</u>

: None).

### **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing agents Water spray or cloud

The product does not burn, use fire-fighting measures appropriate for the surrounding fire.

Unsuitable extinguishing agents do not use a jet of water to extinguish

### 5.2. Special hazards arising from the substance or mixture

Specific risks Exposure to fire may cause containers to rupture and explode

Hazardous combustion products None).

#### 5.3. Advice for firefighters

Specific methods

Use extinguishing media suitable for the surrounding fire. Exposure to fire and heat may cause gas containers to rupture. Cool exposed containers with water spray from a protected location. Do not

allow watering water used in emergency cases to flow into the gutters.

If possible, stop the gas flow.

Use water spray or cloud to reduce the fumes to the ground if possible

Move containers from fire area if it can be done without risk.

Special protective equipment for firefighters In confined spaces use a personal self-contained breathing apparatus (SCBA).

Protective clothing and self-contained breathing equipment for firefighters

Standard EN 137 - Autonomous open circuit compressed air device with a full face mask. Standard EN 469: protective clothing for firefighters. Standard EN 659: Protective gloves

For firefighters

### SECTION 6: Measures to be taken in the event of accidental release

# 6.1. Personal precautions, protective equipment and emergency procedures

For non-rescuers Act according to the local emergency plan.

> Try to stop the leak Evacuate the area.

 $\label{thm:ensure} \textbf{Ensure adequate air ventilation.}$ 

Use protective clothing.

Prevent the product from entering sewers, basements, pits, or any other location where its

accumulation could be dangerous.

Stav upwind.

See section 8 of the SDS for more information on personal protective equipment

For first aiders Wear a self-contained breathing apparatus (SCBA) when entering the area unless you have verified

that it is safe.

Oxygen detectors should be used when asphyxiating gases may be released.

See section 5.3 of the SDS for more information

6.2. Precautions for environmental protection

Try to stop the leak.

6.3. Methods and material for containment and cleaning up

Ventilate the area

6.4. Reference to other SECTIONS

See also sections 8 and 13

### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Safety when using the product The product must be handled in accordance with good industrial hygiene and safety procedures.

SARL RAYANOX ZA Bethioua Wilaya of Oran,



Safety when handling the gas container

# **Food grade ARGON**

Issue date: 10/14/2021 Replaces sheet: 4.0 Revision date: 10/14/2021 Version: 6.0

SDS reference: EIGA003A

Only persons with appropriate experience and training should handle gases under pressure.

Consider adding pressure safety valve(s) to the installation.

You ensure that the entire gas installation has been (or is regularly) checked for the absence of

leaks, before use

Do not smoke while handling the product.

Use only specified equipment appropriate for this product and its operating pressure and

temperature. Contact your gas supplier if in doubt.

Avoid the return of water, acids and alkalis

Use only with cleaned equipment approved for oxygen use and calculated for cylinder pressures

Avoid the return of water, acids and alkalis.

Do not breathe the gas.

Avoid letting the product into the air

Refer to the supplier's instructions for handling the container.

Prohibit products from rising into the container

Protect cylinders from physical damage, do not pull, roll, slide, drop To move the bottles even a short distance, use a cart (bottle rolls,

etc.), designed for transporting bottles

Leave the tap protection cap in place until the container is again secured either by a wall or support  $% \left\{ \left( 1\right) \right\} =\left\{ \left( 1$ 

or placed in a container or placed in position for use.

If the user encounters any difficulty opening or closing the cylinder valve, the user should

discontinue use and contact the supplier

Never attempt to repair or modify a container valve or its pressure relief devices.

Damaged faucets should be reported immediately to the supplier

 $\label{lem:containers} \mbox{Keep tap outlets from containers clean and not contaminated, particularly with oil or water.}$ 

If the container has been equipped with one, as soon as it has been disconnected from the

installation, replace the cap or the tap outlet cap.

Close the container tap after each use and when empty, even if it is still connected to the  $\ensuremath{\mathsf{I}}$ 

equipment.

Never attempt to transfer gases from a bottle/container into another container.

Never use a direct flame or electric heater to increase the pressure in the container.

Do not remove or damage the labels put by the supplier to identify the contents of the bottle. Prevent water from being drawn into the container.

Open the tap slowly to avoid a sudden build-up of pressure (water hammer).

### 7.2. Conditions for safe storage, including any incompatibilities

Follow all local regulations and requirements for container storage.

Containers should not be stored in conditions likely to aggravate corrosion.

Container valve covers or caps must be in place.

Containers must be stored in an upright position and secured to prevent falling.

Containers in stock should be periodically checked for general condition and absence of leaks.

Store the container in a well-ventilated area, at a temperature below 50°C In storage, separate flammable gases and other flammable materials

Store containers in areas not exposed to the risk of fire and away from sources of heat and ignition.

Keep away from combustible materials

#### 7.3. Specific end use(s)

: None)

### SECTION 8: Exposure controls/personal protection

# 8.1. Control Settings

OEL (Occupational Exposure Limits) : Not available.

DNEL (Derived No Effect Dose) : Not available.

PNEC (Predicted No Effect Concentration(s)) : Not available.

#### 8.2. Exposure controls

#### 8.2.1. Appropriate technical controls

Maintain appropriate exhaust ventilation locally and overall.

Pressure equipment should be checked regularly for leaks

Gas detectors should be used when oxidizing gases are likely to be released

Think about work permits, e.g. for maintenance.

### 8.2.2. Personal protective equipment

Eye/face protection

A risk analysis of the use of the product must be conducted and documented in all workplaces affected by the use of the product in order to choose personal safety equipment regarding the identified risks. The following recommendations should be considered

Choose Personal Protective Equipment that complies with recommended EN/ISO standards. Wear tight safety glasses and a face shield when transferring or disconnecting transfer lines.

Standard EN 166 - Individual eye protection - Specifications.

SARL RAYANOX
ZA Bethioua Wilaya of Oran,
EN: French



Issue date: 10/14/2021 Replaces sheet: 4.0 Revision date: 10/14/2021 Version: 6.0

SDS reference: EIGA003A

Skin protection

Hand protection
 Wear protective gloves when handling gas cylinders.

Standard EN 388-Protective gloves against mechanical risks.

-Miscellaneous Wear safety shoes when handling cylinders.

Standard EN ISO 20345: Personal Protective Equipment - safety shoes.

Respiratory protection
 Self-contained breathing apparatus (SCBA) or mask with positive pressure air supply should be used

in under-oxygenated atmospheres.

Standard EN 137 - Autonomous open circuit compressed air device with full face mask

Thermal risks No additions to previous sections.

8.2.3. Ambient exposure controls

None are necessary.

## **SECTION 9: Physical and chemical properties**

#### Information on essential physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa
 Color
 : Gaseous
 : Colorless.

Smell : Not detectable by odor

Olfactory threshold : Detection of thresholds by smell is subjective and inappropriate for warning in the event of

overexposure

pH : Not applicable to gases and gas mixtures.

Melting point / Freezing point :-189°C
Boiling point :-186°C

Flash point : Not applicable to gases and gas mixtures. Evaporation rate : Not applicable to gases and gas mixtures.

Flammability (solid, gas) : Non-flammable. : Non-flammable. **Explosive limits** Vapor pressure [20°C] : Not applicable. Vapor pressure [50°C] : Not applicable. Vapor density : Not applicable. Relative density, liquid (water=1) : Not applicable. Relative density, gas (air=1) : 1.38 Water solubility : 67.3 mg/l

Partition coefficient n-octanol/water (Log Kow) : Not applicable to inorganic gases

Auto-ignition temperature : Non-flammable.
Decomposition temperature : Not applicable.

Viscosity : No reliable data available.

Explosive properties : Not applicable.

Oxidizing properties : Not applicable.

**Other information** 

Molar mass 40 g/mol Critical temperature [°C] -122°C

Other data Gas or vapor heavier than air. May accumulate in confined areas, especially in low areas and

basements

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

No reactivity hazard other than the effects described in the sections below

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None).

10.4. Conditions to avoid

Avoid humidity in installations.

10.5. Incompatible materials

For further information on compatibility, refer to ISO 11114.

Consult supplier for specific recommendations

**10.6.** Hazardous decomposition products : None).

# **SECTION 11: Toxicological information**

SARL RAYANOX
ZA Bethloua Wilaya of Oran,
EN: French
EN: French



Issue date: 10/14/2021 Replaces sheet: 4.0 Revision date: 10/14/2021 Version: 6.0

: No known effects with this product.

: No known effects with this product.

: No known effects with this product.

: No known effects with this product. : No known effects with this product.

: No known effects with this product.

: No known effects with this product.

: No known effects with this product.

: No known effects with this product.

: This product has no known toxicological effects.

SDS reference: EIGA003A

11.1. Information on toxicological effects

acute toxicity Skin corrosion/irritation

Serious eye damage/eye irritation Respiratory or skin sensitization

**Cell mutagenicity** 

Carcinogenicity

Toxic for reproduction: fertility Toxic for reproduction: fetus

Specific target organ toxicity — single exposure Specific target organ toxicity - repeated exposure

Inhalation hazard

: Not applicable to gases and gas mixtures

**SECTION 12: Ecological information** 

12.1. Toxicity

Assessment EC50 48h - Daphnia magna [mg/l]

EC50 72h - Algae [mg/l]

LC50 96 Hours - fish [mg/I]

12.2. Persistence and degradability

Assessment

12.3. Bioaccumulation potential

Assessment

12.4. Mobility in the ground

Assessment

12.5. Results of PBT and VPVB assessments

Assessment

12.6. Other adverse effects

Other adverse effects

Effect on the ozone layer

Effect on global warming

This product is ecologically safe.

No data available.

No data available.

No data available.

This product is ecologically safe.

This product is ecologically safe.

This product is ecologically safe

Not classified as PBT or vPvB

May cause frost damage to vegetation.

: No effect on the ozone layer.

: None).

**SECTION 13: Disposal Considerations** 

13.1. Waste treatment methods

Can be placed in a well-ventilated area

Do not discharge into any location where its accumulation could be hazardous.

Return the uneaten product to the supplier in its original container

16 05 04: Gases in pressure vessels (including halons) containing substances List of hazardous waste

Dangerous.

13.2. Further information

The treatment and disposal of waste by third parties must be in accordance with local and/or

national legislation.

**SECTION 14: Transport information** 

14.1. UN number

UN number

: 1006

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) Air transport (ICAO-TI / IATA-DGR)

Transport by sea (IMDG)

14.3. Transport hazard class(es)

Labeling

COMPRESSED ARGON Argon, Compressed Argon, COMPRESSED



:2

: 1A : 20

2.2: Non-flammable, non-toxic gases.

: E - Passage prohibited in category E tunnels.

Transport by road/rail (ADR/RID)

Class Classification code

Danger no.

Restriction of passage in tunnels

Transport by sea (IMDG)

Class or division / Subsidiary risk(s)

SARL RAYANOX ZA Bethioua Wilaya of Oran,

Algeria. 041 – 74 – 93 -23/24

EN: French

5/7



Issue date: 10/14/2021 Replaces sheet: 4.0 Revision date: 10/14/2021 Version: 6.0

SDS reference: EIGA003A

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Air transport (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None).
Air transport (ICAO-TI / IATA-DGR) : None).
Transport by sea (IMDG) : None).

14.6. Special precautions to be taken by the user

Packaging instruction(s)

Transport by road/rail (ADR/RID) : P200

Air transport (ICAO-TI / IATA-DGR)

Passenger and cargo aircraft : 200
Cargo plane only : 200
Transport by sea (IMDG) P200

Precautionary measures for transport Avoid transport in vehicles where the load compartment is not separated from the driver's cab.

Ensure that the vehicle driver is aware of the potential hazards of the load and the steps to take in

the event of an accident or other emergency situation.

Before transporting containers:
Ensure there is adequate ventilation.
Make sure containers are firmly secured

Make sure the cylinder valve is closed and not leaking

Make sure that the faucet outlet protection cap (if it exists) is correctly in place. Ensure that the tap protection device (if it exists) is correctly put in place

14.7. Transport in bulk in accordance with Annex II of the Marpol Convention and the IBC Code

: Not applicable.

### **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific to the substance or mixture

**EU regulations** 

Employment restrictions : None).
Seveso Directive 2012/18/EU (Seveso III) : Not covered

**National guidelines** 

National regulations: : Ensure that all national or local regulations are followed.

**Chemical Safety Assessment** 

:A Chemical Risk Assessment (CSA) does not need to be carried out for this product.

### **SECTION 16: Other information**

Indications of change : None).

Abbreviations and acronyms

**ETA-Estimate of Acute Toxicity** 

CLP- Classification Labeling Packaging - Regulation (EC) No 1272/2008 relating to classification,

labeling and packaging.

REACH - Registration, Evaluation, Authorization and Restriction of Chemicals – Regulation (EC) No 1907/2006 concerning the registration, evaluation and authorization of chemical substances, as

well as the restrictions applicable to these substances.

EINECS - European Inventory of Existing Commercial Chemical Substances - Inventory

European marketed chemical substances

CAS number - numerical identifier assigned by the Chemical Abstract Service (USA)

PPE - Personal protective equipment

LC50 - Lethal Concentration - Lethal concentration for 50% of the population tested

RMM-Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic.

vPvB - very (very) Persistent and very (very) Bioaccumulative.

STOT - SE: Specific Target Organ Toxicity - Single Exposure; Specific target organ toxicity - Single

exposure.

SARL RAYANOX
ZA Bethioua Wilaya of Oran,
EN: French
6/7

041 – 74 – 93 -23/24



Issue date: 10/14/2021 Replaces sheet: 4.0 Revision date: 10/14/2021 Version: 6.0

SDS reference: EIGA003A

CSA - Chemical Safety Assessment

EN - European Norm - European Standard

UN - United Nations - United Nations

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA - International Air Transport Association - International Air Transport Association

IMDG Code - International Maritime Dangerous Goods Code - Code for maritime transport

: The risks of asphyxiation are often underestimated and must be emphasized during operator training.

Before using this product for a new application or for testing, a thorough material compatibility study and risk analysis should be performed.

The information given in this document is believed to be accurate at the time of printing.

Despite the care taken in drafting this document, no liability can be accepted in the event of damage or accident resulting from its use.

**Training Tips** 

DISCLAIMER OF LIABILITY

SARL RAYANOX ZA Bethioua Wilaya of Oran, Algeria. 041 – 74 – 93 -23/24